

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/24300 A1

(51) International Patent Classification⁷: H01M 8/10, 4/66

(21) International Application Number: PCT/AU00/01187

(22) International Filing Date:
28 September 2000 (28.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 3154 29 September 1999 (29.09.1999) AU

(71) Applicant (for all designated States except US): CE-
RAMIC FUEL CELLS LIMITED [AU/AU]; 170
Browns Road, Noble Park, Victoria 3174 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JAFFREY, Donald

[AU/AU]; 2 Bonnieview Road, Mount Dandenong, Victo-
ria 3767 (AU). FOGER, Karl [AT/AU]; 2 Macartney Av-
enue, Kew, Victoria 3101 (AU).


(74) Agents: HUNTSMAN, Peter, Harold et al.; Davies Colli-
son Cave, 1 Little Collins Street, Melbourne, Victoria 3000
(AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: FUEL CELL ASSEMBLY



(57) Abstract: A tubular fuel cell assembly (10) comprising an anode side defining a tubular passage (14) for fuel gas, the anode side comprising an anode layer (12) and an anode-side current collector in electrical contact with the anode layer, a solid oxide electrolyte layer (18) on a radially outer surface of the anode layer, a cathode layer (20) on a radially outer surface of the electrolyte layer, and a cathode-side current collector on the cathode layer, wherein the anode-side current collector comprises a tubular metallic structure which is adapted to permit fuel gas in the passage to contact the anode layer, at least the surface of the tubular metallic structure being formed of Ni or Ni alloy, and wherein the tubular metallic structure is at least partly embedded in the anode layer.

WO 01/24300 A1



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *With international search report.*